## Please allow 24 hours' notice for inspections 664-9727

	FOR DI	STRICT USE ONLY	PERMIT NUMBER			
	PERMI	T TYPE: NEW / RI	EP / CAP / MHCAP	ACCT #:		
			/ VACUUM / GRINDER			
	SEWER	R EXTENSION: PR	VATE / PUBLIC	PROP CODE:		
S	OUTH AND C	ENTER CHAUTAU	QUA LAKE SEWER DIST	RICTS BUILDING SEWER	PERMIT APPLICATION	
l, th	e undersigned,	(Oversorle Na	me)	being the owner of the	e property located at	
		(Owner's Na	me)			
	(Number)		treet)	do hereby requ	est a permit to (circle one):	
	,	•	,			
Inst	all / Repair / Ca <sub>l</sub>	p a building sewer t	nat connects the		at said location, described as	
	,		in the Tov	n/Village of	·	
	(Section)	(Block)	(Lot)			
1.	The name and a	address of the persor	or firm who will perform the p	roposed work is		
Lis	st all subcontract	ors that will be perfor	ming work and the type of wor	k		
	Three Insurance	e Forms Required for	a Permit for Each Contractor	Performing Work		
	1. "ACORI	D" Certificate of Liabil	ity showing General, Automob	ile, and Umbrella Liability with	a limit of One Million Dollars.	
			gation waiver must be included	d for all 3 policies and Chauta	uqua County must be listed	
		ally as additional insu 3 Form 105.2 <b>OR</b> For	rea. n 26.3 Verifying Worker's Con	npensation Coverage.		
	<ol><li>EITHER</li></ol>	Form DB120.1 <b>OR</b> F	orm DB155 Verifying NYS Dis	sability.		
					eet, Mayville, NY 14757-1007.	
			ree forms and must be curre		of the homeowner's insurance	
					ation showing a limit of liability of	
		00 in place of the abo	•	brintiod with the permit applie	anon onowing a limit of hability of	
		·	•			
2.	Plans and speci SCHEMATIC D	fications for the property	osed building sewer are attach	ed hereto. ALL PERMITS M	UST BE ACCOMPANIED BY A	
	OONLINATIO D	<del>KAVIIIO</del> .				
3.	The permit appl	ication for a new con	nection must be signed by the	owner holding legal title to the	e property and accompanied by	
	a fee of: Fifty D	ollars (\$50) for one o	r two family residential structu	res; One Hundred Fifty Dollar	s (\$150) for properties producing	
	or reasonably e	xpected to produce in Junty Local Law 6-941	dustrial wastes [Note: A disch and One Hundred Dollars (\$	arge permit may also be requ 100) for other uses. <b>NO</b> permi	t fee is required for caps or	
	repairs.	and Local Law 6 6 1	, and one handred behalf (p	100) 101 011101 00001 <u>110</u> politil	troo to required for eaps of	
4	Once the building	na lateral sewer insta	lation has been installed test	ed and inspected and approve	ed by the Districts, the owner will	
٦.	be placed on the	e Districts' billing rolls	on the next quarterly billing c	ycle and shall be billed in acco	ordance with the current scale	
			are for the benefit of the Count			
			ce no guarantees or warrantee Districts' inspection or approv		Imponents or areas and not	
Data.	•					
Date:			Signea: _	(Applicant)		
Δddr	266.			ne:		
Owne	er's Phone #:	and parmit issued for	 a period of 90 days (180 days	for cower extensions) from th	a data of approval in	
accor	dance with and s	subject to Chautauqua	a period of 90 days (180 days i County Local Law 6-94 and a	all other applicable laws and re	e date of approval in egulations.	
			•	• •	-	
Appro	oveu Dale		Signed: Director - South an	d Center Chautauqua Lake S	ewer Districts	

NOTE: Inspectors are not available Federal holidays, weekends or after 2:30 PM weekdays. Exceptions can be made with prior consent of the Director. The excavation may not be backfilled until the inspection has been completed.

## Please allow 24 hours' notice for inspections 664-9727

Listed below are several common requirements that must be met when installing or repairing sewer laterals.

This list is <u>not</u> all inclusive. There may be other requirements that must be met depending upon the specific installation. It is the responsibility of the permit signatory to ensure compliance with all requirements of Chautauqua County Local Law 6-94.

- All pipe shall be minimum 4" diameter PVC, Schedule 40, SDR-21 or SDR-35 (Note: SDR-35 is not acceptable for vacuum sewer laterals)
- All laterals shall be laid at a minimum slope of ¼" per foot
- All laterals shall be installed with a minimum depth of cover of 48"
- When laterals are to be installed parallel to a foundation wall, a minimum distance of 36" shall be maintained
- A cleanout shall be installed just inside or just outside the building with a wye fitting in the direction of flow and shall be brought to final grade and appropriately capped, if installed outside
- Additional cleanouts shall be installed at a minimum of every ninety (90) feet along the lateral with a wye fitting in the direction of flow and shall be brought to final grade and appropriately capped
- No 90-degree fittings shall be permitted, if a 90-degree bend is required, it shall be made using two 45-degree fittings with a minimum of 6" of pipe between fittings
- All pipe shall be bedded with a minimum of 6" of pea gravel on all four sides (Note: do not place pea gravel on top
  of pipe until inspection has been completed)
- All laterals shall be subject to a hydrostatic or air pressure leak test; The installer is responsible for plugging each end of the lateral and filling the pipe with water or air; The water level in the stand pipe shall drop no more than ½" in twenty (20) minutes; The air pressure shall drop no more than 1 psi in 3 ½ minutes
- All laterals shall be inspected by a Sewer District inspector prior to being backfilled

The undersigned acknowledge:	s that he/she has	read the above	requirements a	and understands	that additional
requirements may need to be n	net, according to C	Chautauqua Co	unty Local Law	6-94	

Signed:		Date:		
	(Applicant)			

NOTE: Inspectors are not available Federal holidays, weekends or after 2:30 PM weekdays. Exceptions can be made with prior consent of the Director. The excavation may not be backfilled until the inspection has been completed.